Applications

NORD

210CC/320CC/SRA3 Plus

Features

- Full bleed cutting.
- · Long blade life.
- Highest accuracy.
- Mark reader equipped.
- · Most flexible formats in its class.
- Tandem paper feed system for coated paper.
- $\bullet \, {\sf Sheet} \, \, {\sf thickness} \, {\sf compensation} \, {\sf separator} \, {\sf adjustment}.$
- Handles card stock form 180 gsm to 300 gsm no adjustment needed.
- Adjustable first cut length and for follow on cuts to take into account image drift.
- Standard fitment mark reader for automatic self adjustment for compensation of variable image drift .

aumor

320CC

Specification

In-feed paper size SRA3 or A3
Paper weight 180-300GSM
Slitting width 85/90mm

Out put paper size 85×45mm,85×50mm,85×54mm,85×95mm,85×127mm

90×45mm,90×50mm,90×54mm,90×95mm,90×127mm

Output column 3 Tray capacity 8mm

Expandable tray capacity 127mm/ about 20kg **Process speed** About 80 sheets/minute

Dimensions 800×500×700mm
Operation Display LCD Panel
Power Supply 220V/50HZ



Stacker



Output roller

210CC

Specification

In-feed paper size A4 or SRA4
Paper weight 180-350GSM
Slitting width 85mm/90mm

 $\textbf{Out put paper size} \qquad 85 \times 45 \text{mm}, 85 \times 50 \text{mm}, 85 \times 54 \text{mm}, 85 \times 95 \text{mm}, 85 \times 127 \text{mm}$

90×45mm,90×50mm,90×54mm,90×95mm,90×127mm

Output column 2 Tray capacity 8m

Process speed About 10 sheets/minute
Dimensions 800×500×600mm

Operation Display LCD Panel
Power Supply 220V/50HZ



Specification

In-feed paper size SRA3 or A3
Paper weight 180-300GSM
Slitting width 50mm

Out put paper size 50×45mm,50×50mm,50×54mm,50×90mm,50×127mm
Output column 5

Tray capacity 8mm

Process speed 15 sheets/minute
Dimensions 800×500×700mm

Operation Display LCD Panel
Power Supply 220V/50HZ



