



## FEATURES

- New Size, up to 380mm / 15" actual laminating width
- High quality thermal encapsulation
- Fast, up to 5m/min / 16.5ft/min
- Large film roll capacity (up to 280mm / 11" diameter)
- Accepts thick substrates (up to 6mm/0.24")
- STAND-BY function: Power saving & Auto shut off



## APPLICATION

- Digital and offset graphics, Outdoor signage, Inkjet & Silk-screened posters, Photo finishing, Large format material, Flexible & Rigid displays, Decaling and Floor graphics.

## ▸ SPECIFICATION

Description	Data
Power Supply	AC 100, 200, 220 ~ 240V 50 / 60Hz 120V 60Hz
Power Consumption	1500 Watts
Max. Laminating Width	380 mm / 15"
Film Thickness	25 - 250 mic / 1 - 10 mil
Max Laminating Speed	5 m/min / 16.4 ft/min
Ready time	8 min
Heating Method	Hot Roller
Drive Motor	DC Geared
Max. Temp. Control	150 C / 302 F
Speed Control	9 settings
Transport Type	4 Roller
Film Core Size	1", 2.25", 3"
Cooling System	No
Side Cutter	No
Cross Cutter	Yes
Film Alignment	No
Hot Lamination	Yes
Cold Lamination	No
Mounting Thickness	6 mm / 0.24"
Take Up System	No
Paper Counter	No
Length Measurement	No
Reverse	Yes
Remote Control	No
Foot Pedal	No
Unit Dimensions (WxDxH)	550 x 690 x 605 (mm) 21.5" x 27" x 24"
Unit Weight	45 kg / 99 lbs
Carton Dimensions (WxDxH)	800 x 750 x 650 (mm) 31.5" x 29.5" x 25.5"
Carton Weight	72 kg / 159 lbs