$oldsymbol{M3000Np}$ Series Notebook PC



Robust Simplicity www.asus.com.tw Rev 0.3 Nov 25, 2003

2-Spindle, Pentium-M 14"XGA/SXGA+ LCD & 855GME

•	~ .	•
Speci	#10N#	10110
MIPLE	,,,,,,,	
Speci	, ecui	0110

Processor & Cache

- Intel Pentium-M® Processor with 1MB cache
- Intel Dothan with 2MB L2 cache
- Speed 1.3 GHz~2GHz
- uFC-PGA package

BIOS

■ AMI 4MB Flash EPROM, PMU, Plug & Play

Chipset

■ Intel 855GME & ICH4

Main Memory

- 2 x SODIMM sockets for expansion up to 2GB (BTO
- 0MB on board memory
- DDR333 DRAM support (SODIMM)

Display

14.1" active matrix TFT, XGA/SXGA+, 256K colors max

Graphics & Video Module

■ Embedded 855 GM+ internal Gfx

CRT Display Modes

- VGA 640 x 480, 256/32K/64K/16.7M colors
- SVGA 800 x 600 256/32K/64K/16.7M colors
- XGA 1024 x 768 256/32K/64K/16.7M colors
- SXGA 1280 x 1024 256/32K/64K/16.7M colors
- UXGA 1600x1200 256/32K/64K/16.7M colors

PC Card Slot

- PCMCIA 2.1 supports one Type II
- 32-bit PC CardBus 1.0 architecture

Hard Disk Drive

- 2.5" 9.5mm IDE HDD /w Ultra DMA/100 / S.M.A.R.T.
- 7200/5400/4200 RPM support
- Capacities of 20/40/60/80 GB (BTO option)

Network Connectivity

- MiniPCI options of
 - ♦ Intel Wireless Pro module supports 802.11 a/b; b/g (BTO option)
 - ◆ ASUS WLAN 802.11 b/g (BTO option)
- Integrated universal PPT v.92 MDC Fax/ Modem (BTO
- AC Link Ver. 2.1 Compliant and V.92 / K56flex support
- 10/100 Mbps LAN built-in

Modular Bay

- One modular bay with choices of
 - ◆ 5.25"/12.7mm DVD-ROM
 - 5.25"/ 12.7mm DVD & CD-RW combo drive
 - 5.25"/12.7mm DVD-RW
 - 2nd 2.5"/9.5mm HDD
 - 2nd battery module
- Traveler's drawer ■ Hot-Swap capable

LED Status Indicator

- Power on/Suspend, Battery Charging/Low, Storage Access, Caps Lock, Number Lock, Email, 802.11 Acess/Activity,

Keyboard /Instant Keys

- Desktop-Like full-size 85/86/88key
- Four instant keys (Internet, Email, P4Gear, touchpad-lock)

Interface

Hot Keys

Audio

Power

- One VGA port/Mini D-sub 15-pin for external display
- Four USB 2.0 ports
- One EPP/ECP parallel port/D-sub 25-pin
- Two Audio jacks: Head phone or SPDIF, Mic-in
- One RJ-45 for modem
- One RJ-11 for LAN
- One 1394 B Type jack
- One Infrared ports support IrDA
- One PortBarIII 68 pin connector

■ Instant launch keys

- 4 buttons
- Internet, Email, P4 Gear, touchpad-lock
- Function keys
 - Fn+F1 Suspend enable
 - Fn+F2 Wireless LAN on/off switch
 - Fn+F5 Brightness down
 - Fn+F6 Brightness up
 - Fn+F7 LCD on/off switch
 - Fn+F8 LCD/CRT display switch
 - Fn+F10 Mute
 - Fn+F11 Volume down
 - Fn+F12 Volume up

■ Built-in AC'97 compliant audio chip, with 3D effect & full duplex

- Built-in stereo speakers and microphone.

■ Stand-by, Suspend to Disk, and Suspend to RAM Management

- APM 1.2 and ACPI 2.0 supported

Battery Pack &

- Primary: Li-Ion 8 cells, 14.8V, 4400mAh, 65W battery
- Secondary battery available(using modular bay)
- Battery life 6.5 hrs(10hr with 2nd battery)
- Charging time, 2.5 hrs Quick charge 90% (Power off) / 4hrs (Power on)
- Battery low warning under Windows environment
- Enters Save-To-Disk mode automatically if less than 5%
- Output: 19V DC, 3.42A, 65W

AC adapter ■ Input: 100~240V AC, 50/60Hz universal

- Built-in touchpad
 - 4 click buttons to support scroll up/down key
 - Support touchpad-lock function

25 W thermal envelop

- High-exchange efficiency copper molding heat sink with heat-pipes
- Temperature-Controlled cooling fan

Dimension /Weight

Security

Pointing

Device

Heat

Dissipation

- 309 x 254x 29mm
- **2.27** kg
- Kensington Lock hole
- BIOS setup, Power on, HDD user password protection